Spabond 540 Slow Hardener

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878
Issue date: 10/09/2015 Revision date: 20/03/2024 Supersedes version of: 14/08/2023 Version: 8.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	:	Mixture
Name	:	Spabond 540 Slow Hardener
UFI	:	TG6J-7117-V00H-CUR5
Product code	:	15848
Type of product	:	Hardener (Crosslinker)
Product group	:	Hardener

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use,Professional use

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Gurit (UK) Ltd
St Cross Business Park
Newport
GBR PO30 5WU Isle of Wight
United Kingdom
T +44 (0) 1983 828 000 (All Technical and Commercial Enquiries)
Regulatory@Gurit.com, www.gurit.com

Other
Gurit Spain SA
Polígono Industrial Romica C/K
Parcela 11C, APDO.447
ESP 02080 Albacete
Spain
T +34 967 254 507, F +34 967 254 005
Regulatory@gurit.com, www.Gurit.com

1.4. Emergency telephone number

Emergency number : Carechem 24Hrs: +44 (0) 1273 289451
Telephone number for use in case of chemical exposure, spillage or fire only.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 1, Sub-Category 1B	H314
Serious eye damage/eye irritation, Category 1	H318
Skin sensitisation, Category 1	H317
Reproductive toxicity, Category 2	H361
Specific target organ toxicity – Repeated exposure, Category 2	H373
Hazardous to the aquatic environment – Chronic Hazard, Category 3	H412

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Suspected of damaging fertility. Suspected of damaging the unborn child. (if inhaled). May cause damage to organs (liver, skeletal muscle) through prolonged or repeated exposure (if inhaled). Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious eye damage. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS05 GHS07 GHS08

Signal word (CLP) : Danger

Contains : 2-piperazin-1-ylethylamine; Propylene glycol diamine, 2-amino-, diether with Propylene

Hazard statements (CLP) : H314 - Causes severe skin burns and eye damage.
H317 - May cause an allergic skin reaction.
H361 - Suspected of damaging fertility. Suspected of damaging the unborn child. (if inhaled).
H373 - May cause damage to organs (respiratory tract) through prolonged or repeated exposure (if inhaled).
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP) : P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P260 - Do not breathe vapours.
P264 - Wash hands thoroughly after handling.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P273 - Avoid release to the environment.

2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

Component	
Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII	4-tert-butylphenol (98-54-4)
Substance(s) not meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII	4-tert-butylphenol (98-54-4)

The mixture contains substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

Component	
Substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605	4-tert-butylphenol (98-54-4)

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Propylene glycol diamine, 2-amino-, diether with Propylene	CAS-No.: 9046-10-0 EC-No.: 618-561-0 REACH-no: 01-2119557899-12	10 – 25	Skin Corr. 1C, H314 Eye Dam. 1, H318 Aquatic Chronic 3, H412

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
2-piperazin-1-ylethylamine	CAS-No.: 140-31-8 EC-No.: 205-411-0 EC Index-No.: 612-105-00-4 REACH-no: 01-2119471486-30	5 – 10	Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Repr. 2, H361 STOT RE 1, H372 Aquatic Chronic 3, H412
benzyl alcohol	CAS-No.: 100-51-6 EC-No.: 202-859-9 EC Index-No.: 603-057-00-5 REACH-no: 01-2119492630-38	1 – 3	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2, H319
4-tert-butylphenol substance listed as REACH Candidate substance identified as having endocrine disrupting properties	CAS-No.: 98-54-4 EC-No.: 202-679-0 EC Index-No.: 604-090-00-8 REACH-no: 01-2119489419-21	< 1	Skin Irrit. 2, H315 Eye Dam. 1, H318 Repr. 2, H361f STOT SE 3, H335 Aquatic Chronic 1, H410

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Rinse skin with water/shower. Take off immediately all contaminated clothing. Call a physician immediately.
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion : Rinse mouth. Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact : Burns. May cause an allergic skin reaction.
Symptoms/effects after eye contact : Serious damage to eyes.
Symptoms/effects after ingestion : Burns.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Precautionary measures fire : Evacuate area.
Firefighting instructions : Exercise caution when fighting any chemical fire.

Protection during firefighting	:	Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information	:	Collect contaminated fire fighting water seperately. It must not enter drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment	:	Protective clothing.
Emergency procedures	:	Ventilate spillage area. Do not breathe vapours. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment	:	Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	:	Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	:	Collect spillage.
Methods for cleaning up	:	Mechanically recover the product. Notify authorities if product enters sewers or public waters.
Other information	:	Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13. For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	:	Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Do not breathe vapours. Avoid contact with skin and eyes.
Hygiene measures	:	Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Separate working clothes from town clothes. Launder separately. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	:	Store locked up. Store in a well-ventilated place. Keep cool.
Storage temperature	:	≤ 30 °C Possible pressure build-up
Storage area	:	Store away from heat. Store in a well-ventilated place.
Special rules on packaging	:	Keep only in original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

No additional information available

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:
Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:
Safety glasses

8.2.2.2. Skin protection

Skin and body protection:
Wear suitable protective clothing

Skin and body protection	
Type	**Standard**
Tyvek® Gown/Coveralls	EN 13034

Hand protection:
Protective gloves. Time of penetration is to be checked with the glove producer

Hand protection					
Type	**Material**	**Permeation**	**Thickness (mm)**	**Penetration**	**Standard**
Disposable gloves	Nitrile rubber (NBR)	0 (< 10 minutes)	0.26mm		EN ISO 374

8.2.2.3. Respiratory protection

Respiratory protection:
[In case of inadequate ventilation] wear respiratory protection. Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

Respiratory protection			
Device	**Filter type**	**Condition**	**Standard**
Disposable half mask	Gas/vapour filter	Vapour protection	EN 405

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:
Avoid release to the environment.

Other information:
Industrial and professional. Perform risk assessment prior to use. Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	:	Solid
Colour	:	Green.
Appearance	:	Paste.
Odour	:	Amine-like.
Odour threshold	:	Not available
Melting point	:	Not available
Freezing point	:	Not applicable
Boiling point	:	Not available
Flammability	:	Non flammable.
Explosive properties	:	Product is not explosive.
Lower explosion limit	:	Not applicable
Upper explosion limit	:	Not applicable
Flash point	:	Not applicable
Auto-ignition temperature	:	Not applicable
Decomposition temperature	:	Not available
pH	:	≈ 10
pH solution	:	Not available
Viscosity, kinematic	:	Not applicable
Viscosity, dynamic	:	25 °C
Solubility	:	Not available
Partition coefficient n-octanol/water (Log Kow)	:	Not available
Vapour pressure	:	Not available
Vapour pressure at 50°C	:	Not available
Density	:	1,06 g/cm³
Relative density	:	Not available
Relative vapour density at 20°C	:	Not applicable
Particle size	:	Not available

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content	:	0 g/l
Bulk density	:	≈ 1,06 g/cm³

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport. Product is not explosive.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

benzyl alcohol (100-51-6)	
LD50 oral	1580 mg/kg bodyweight Animal: mouse, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1410 - 1770
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: EPA OTS 798.1100 (Acute Dermal Toxicity), Remarks on results: other:
LC50 Inhalation - Rat	> 4178 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Remarks on results: other:

2-piperazin-1-ylethylamine (140-31-8)	
LD50 oral	2140 mg/kg
LD50 dermal rabbit	866 mg/kg

Propylene glycol diamine, 2-amino-, diether with Propylene (9046-10-0)	
LD50 oral rat	2885 mg/kg
LD50 dermal rabbit	2980 mg/kg

4-tert-butylphenol (98-54-4)	
LD50 oral rat	2100 mg/kg
LD50 dermal rabbit	2318 mg/kg

Skin corrosion/irritation : Causes severe skin burns.
pH: ≈ 10

Propylene glycol diamine, 2-amino-, diether with Propylene (9046-10-0)	
pH	11,6

Serious eye damage/irritation : Causes serious eye damage.
pH: ≈ 10

Propylene glycol diamine, 2-amino-, diether with Propylene (9046-10-0)	
pH	11,6

Respiratory or skin sensitisation : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Suspected of damaging fertility. Suspected of damaging the unborn child. (if inhaled).
STOT-single exposure : Not classified

4-tert-butylphenol (98-54-4)	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure : May cause damage to organs (respiratory tract) through prolonged or repeated exposure (if inhaled).

benzyl alcohol (100-51-6)	
NOAEL (oral, rat, 90 days)	400 mg/kg bodyweight Animal: rat, Guideline: other:

2-piperazin-1-ylethylamine (140-31-8)	
STOT-repeated exposure	Causes damage to organs (respiratory tract) through prolonged or repeated exposure (inhalation).

Aspiration hazard : Not classified

benzyl alcohol (100-51-6)	
Viscosity, kinematic	0,005 mm²/s

Propylene glycol diamine, 2-amino-, diether with Propylene (9046-10-0)	
Viscosity, kinematic	10,8 mm²/s

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Component	
4-tert-butylphenol (98-54-4)	The substance is identified for having endocrine disrupting properties but there is no additional data available (see section 2.3)

11.2.2. Other information

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short–term (acute) : Not classified

Hazardous to the aquatic environment, long–term (chronic) : Harmful to aquatic life with long lasting effects.

benzyl alcohol (100-51-6)	
LC50 - Fish [1]	460 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	230 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	770 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	500 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	76828 mg/l Test organisms (species): other:
NOEC chronic fish	48897 mg/l Test organisms (species): other: Duration: '30 d'

2-piperazin-1-ylethylamine (140-31-8)	
LC50 - Fish [1]	1950 – 2460 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 - Fish [2]	> 1000 mg/l (Exposure time: 96 h - Species: Poecilia reticulata [semi-static])
EC50 - Crustacea [1]	32 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h - Algae [1]	495 mg/l (Species: Pseudokirchneriella subcapitata)

4-tert-butylphenol (98-54-4)	
LC50 - Fish [1]	4,71 – 5,62 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 - Fish [2]	6,9 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [static])
EC50 - Crustacea [1]	3,9 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 - Crustacea [2]	3,4 – 4,5 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 72h - Algae [1]	11,2 mg/l (Species: Desmodesmus subspicatus)

12.2. Persistence and degradability

Spabond 540 Slow Hardener	
Persistence and degradability	Rapidly degradable

benzyl alcohol (100-51-6)	
Persistence and degradability	Rapidly degradable

2-piperazin-1-ylethylamine (140-31-8)	
Persistence and degradability	Rapidly degradable

Propylene glycol diamine, 2-amino-, diether with Propylene (9046-10-0)	
Persistence and degradability	Rapidly degradable

4-tert-butylphenol (98-54-4)	
Persistence and degradability	Rapidly degradable

12.3. Bioaccumulative potential

benzyl alcohol (100-51-6)	
Partition coefficient n-octanol/water (Log Pow)	1,1

2-piperazin-1-ylethylamine (140-31-8)	
BCF - Fish [1]	(no bioaccumulation expected)
Partition coefficient n-octanol/water (Log Pow)	-1,48

4-tert-butylphenol (98-54-4)	
BCF - Fish [1]	34 – 240
Partition coefficient n-octanol/water (Log Pow)	2,44

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Component	
Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII	4-tert-butylphenol (98-54-4)
Substance(s) not meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII	4-tert-butylphenol (98-54-4)

12.6. Endocrine disrupting properties

Component	
4-tert-butylphenol (98-54-4)	The substance is identified for having endocrine disrupting properties but there is no additional data available (see section 2.3)

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation : Disposal must be done according to official regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations : Avoid release to the environment. Dispose in a safe manner in accordance with local/national regulations.
Ecological information : Avoid release to the environment.
European List of Waste (LoW, EC 2000/532) : 08 04 09* - waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA

ADR	IMDG	IATA
14.1. UN number or ID number		
UN 3259	UN 3259	UN 3259
14.2. UN proper shipping name		
POLYAMINES, SOLID, CORROSIVE, N.O.S.	POLYAMINES, SOLID, CORROSIVE, N.O.S.	Polyamines, solid, corrosive, n.o.s.
Transport document description		
UN 3259 POLYAMINES, SOLID, CORROSIVE, N.O.S. (2-piperazin-1-ylethylamine ; Propylene glycol diamine, 2-amino-, diether with Propylene), 8, II, (E)	UN 3259 POLYAMINES, SOLID, CORROSIVE, N.O.S. (2-piperazin-1-ylethylamine ; Propylene glycol diamine, 2-amino-, diether with Propylene), 8, II	UN 3259 Polyamines, solid, corrosive, n.o.s. (2-piperazin-1-ylethylamine ; Propylene glycol diamine, 2-amino-, diether with Propylene), 8, II
14.3. Transport hazard class(es)		
8	8	8
		
14.4. Packing group		
II	II	II
14.5. Environmental hazards		
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available		

14.6. Special precautions for user

Overland transport

Classification code (ADR) : C8

Special provisions (ADR)	:	274
Limited quantities (ADR)	:	1kg
Excepted quantities (ADR)	:	E2
Packing instructions (ADR)	:	P002, IBC08
Special packing provisions (ADR)	:	B4
Mixed packing provisions (ADR)	:	MP10
Portable tank and bulk container instructions (ADR)	:	T3
Portable tank and bulk container special provisions (ADR)	:	TP33
Tank code (ADR)	:	SGAN, L4BN
Vehicle for tank carriage	:	AT
Transport category (ADR)	:	2
Special provisions for carriage - Packages (ADR)	:	V11
Hazard identification number (Kemler No.)	:	80
Orange plates	:	
Tunnel restriction code (ADR)	:	E
EAC code	:	2X

Transport by sea

Special provisions (IMDG)	:	274
Limited quantities (IMDG)	:	1 kg
Excepted quantities (IMDG)	:	E2
Packing instructions (IMDG)	:	P002
IBC packing instructions (IMDG)	:	IBC08
IBC special provisions (IMDG)	:	B21, B4
Tank instructions (IMDG)	:	T3
Tank special provisions (IMDG)	:	TP33
EmS-No. (Fire)	:	F-A
EmS-No. (Spillage)	:	S-B
Stowage category (IMDG)	:	A
Segregation (IMDG)	:	SGG18, SG35
Properties and observations (IMDG)	:	Colourless to yellowish solids with a pungent odour. Miscible with or soluble in water. When involved in a fire, evolve toxic gases. Corrosive to most metals, especially to copper and its alloys. Cause burns to skin, eyes and mucous membranes. React violently with acids.

Air transport

PCA Excepted quantities (IATA)	:	E2
PCA Limited quantities (IATA)	:	Y844
PCA limited quantity max net quantity (IATA)	:	5kg
PCA packing instructions (IATA)	:	859
PCA max net quantity (IATA)	:	15kg
CAO packing instructions (IATA)	:	863
CAO max net quantity (IATA)	:	50kg
Special provisions (IATA)	:	A3, A803
ERG code (IATA)	:	8L

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains substance(s) listed on the REACH Candidate List in concentrations ≥ 0.1 % or SCL: 4-tert-butylphenol (EC 202-679-0, CAS 98-54-4)

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Dual-Use Regulation (428/2009)

Contains no substance subject to the COUNCIL REGULATION (EC) No 428/2009 of 5 May 2009 setting up a Community regime for the control of exports, transfer, brokering and transit of dual-use items.

VOC Directive (2004/42)

VOC content : 0 g/l

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes			
Section	**Changed item**	**Change**	**Comments**
	Supersedes	Modified	
	Revision date	Modified	
2.2	Precautionary statements (CLP)	Modified	
2.2	Hazard statements (CLP)	Modified	
9.2	VOC content	Added	
15.1	VOC content	Added	

Full text of H- and EUH-statements:	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Eye Dam. 1	Serious eye damage/eye irritation, Category 1

Full text of H- and EUH-statements:	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H361	Suspected of damaging fertility or the unborn child.
H361f	Suspected of damaging fertility.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Repr. 2	Reproductive toxicity, Category 2
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Corr. 1C	Skin corrosion/irritation, Category 1, Sub-Category 1C
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Skin Corr. 1B	H314	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1	H317	Calculation method
Repr. 2	H361	Calculation method
STOT RE 2	H373	Calculation method
Aquatic Chronic 3	H412	Calculation method

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product The information contained within this document is Gurit copyright and any distribution or publication beyond the recipient's organisation is prohibited without Gurit's prior written consent.